

UO-1302AG SLIM-FIT POU WATER DISPENSER

ACUO
we care about the water you drink



SLIM & SMART

Micro-Computerized Design

Automatic tank refill and ensures all water is boiled before dispensed.

5-Stage Temperature Preservation

RO Filtration only

Allows hot water settings at 98°C, 95°C, 90°C, 80°C or 70°C.

Safety Protection System

Automatically disconnects power and water supply when experiencing malfunction, power or water shortage or leakage.

Safety Indicators

Alerts users when hot water temperature is too low and cold water temperature is too high. Filter Replacement reminder indicates when filter replacement is required.

Sleep-Mode

Allows setting of 1~60hrs and automatically reactivates when Sleep-Mode is over.

High-Efficiency Heating & Chilling

Outstanding insulation and Temperature Exchange System, using less energy and time to heat and chill water.

Re-Boil

Heats water up to 100°C anytime at the press of a button.

T.D.S. Reading

Monitors water quality when desired.

W335 x D520 x H1325 (mm)

UO-1302AG SLIM-FIT POU WATER DISPENSER

ACUO
we care about the water you drink

DISPLAY & CONTROL PANEL

Easy understanding and operation.



SAFETY HOT WATER TAP

Optional item for additional safety aspect.



BUILT-IN FILTRATION SYSTEM

UF-10P5C DUAL-PURPOSE Super-Refined Activated Carbon Filter

2-in-1 Structure
PP + Activated Carbon



Step One:
5 micron PP Filter
Effectively filters out mud, sand, rust and other particles and sediments.
Step Two:
Activated Carbon Filter
Removes color, odor and extracts chemicals such as chloride, pesticides and heavy metals from the water.



UF-504 60G R.O. Membrane

0.0001 micron filters out virus, germs, toxics and heavy metals such as mercury, cadmium... etc, providing clean and safe drinking water.



UF-21 Disposable Post Activated Carbon Filter

For the final polishing of water in Reverse Osmosis systems, to remove unpleasant taste and odors from the water stored in tank, to produce cleaner, clearer, better tasting water.



SPECIFICATIONS

Model	Type	Voltage	Hot Power Consumption	Cold Power Consumption	Hot Tank	Cold Tank	Warm Tank	Hot Water Capacity	Cold Water Capacity
UO-1302AG	Cold / Warm / Hot	110V/220V	1000W	215W	10L	3.3L	5L	20L / HR	14L / HR

*Voltage can be customized based on requirement.
Hot Water 90°C±10°C : Cold Water 15°C±10°C*