

HD CCTV TESTER 8K H.265

IP Camera Test AHD CVI TVI Analog CCTV Tester



Features :

- 4 inch IPS touch screen 960x640 resolution
- 8K H.265 video display via mianstream
- IP and analog display image at the same time
- DC12V 3A, 48V PoE 25.5W power output
- Rapid ONVIF, create the test report and modify IP address
- Hight brightness LED light
- UTP cable test, detect the near-end, mid-end and far-end fault point of the
- RJ45 cable plug
- RJ45 TDR cable test, cable quality test
- SD Card slot, support up to 32G, to save video, picture and other files
- 8MP CVI/TVI/AHD camera test*
- DC12V/3A power output, camera can be powered from 12 Voltage
- Analog camera test, PAL/NTSC auto adapt*

- Auto HD, auto recognize HD coax camera type and resolution, support snapshot, video record & playback, coaxial PTZ Y call OSD menu
- IPC test pro, auto scan all network segments IP, auto open PoE power and display the power. Input username and password, can scan camera image, can batch activate HIKVISION and Dahua cameras, Jump to ONVIF interface and test tools.
- IPC Test (Non-ONVIF test), HIK test tool (Hikvision camera), DH test tool (Dahua camera)
- Rapid Video, just by one key to detect all network camera and auto display Built in
- Wi-Fi, display image from the wireless camera, create Wi-Fi hotspot
- Traffic monitoring, display network port or WIFI connection real-time upload and download speeds and other net
- Customers self-update software, you can install apps with android version, Media player, 4K video files and MKV/MP4 media files play
- Network tool : Ping, IP scan, Port Flash, DHCP server, Trace Route
- Audio in support record and save the audio/LED lamp, caculators, music players and other application tools
- 7.4V/2600mAh Lithium Ion Battery, after 3-4 hours charging, working time lasts 9 hours



Technical Specifications

Model	IPC-1910 Plus
Display	IPS touch screen cctv tester 960x640 resolution
Network port	10/100/1000M auto adjust, RJ45
WIFI	Built in WIFI, speeds 150M, display wireless camera image
H.265 Main Stream test	New hardware decoding, 4K H.265/H.264 camera image display by mainstream testing
IP discovery	Auto-scan the whole network segment camera IP
Rapid ONVIF	Search camera quickly, auto log in and display image from the camera, activate Hikvision camera
IP camera type	ONVIF, ONVIF PTZ, Dahua IPC-HFW2100P, Hikvision DS-2CD864-E13, Samsung SNZ-5200, Tiandy TD-NC9200S2, Kodak IPC120L, Honeywell HICC-2300T, RTSP Viewer
Lens Simulation	can simulate "2.8/3.6/4/6/8/12/16/25mm" lenses display area
Focus information test	camera focus infor, signal quality test, Image quality test.
Analog video test	1 channel BNC Input, NTSC/PAL (Auto adapt)
Snapshot, Video record and playback	Capture current images and record live video as JPG file. Media player will view photos and playback video
PoE power output	48V PoE power output, Max power 25.5W
Working Temperature	-10° C+-50° C
Working Humidity	30% - 90%
Auto Off	1 - 30 mins